

X-MIT™ TRANSMITTER



The Explotrain Model X-MIT Multiple Input Transmitter provides a rugged housing and a simple interface for controlling up to four Explotrain Simulators at distances up to 400m. Four LEDs are each dedicated to a simulator and continuously indicate not only the communications status of the unit, but its Armed/Disarmed and Firing state as well.

Simple push-button operation and color-coded LEDs provide continuous feedback of each Simulator's actions and status.



The X-MIT has no external antenna providing a rugged and water resistant Remote Control option for multiple Explotrain simulators.

(850) 862-5344

info@explotrain.com

www.explotrain.com

Explotrain® LLC
26 Eglin Pkwy SE
Fort Walton Beach, FL 32548



NSN
6110-01-689-7471



TECHNICAL SPECIFICATIONS

LONG RANGE TRANSMITTER CONTROL UNIT	Remote ARM/FIRE/DISARM up to 4 Explotrain® Battlefield Effects Simulators	
# OF CHANNELS	12 ^{1,2}	
USED WITH	X-02™	X-05™
	X-OMG™	X-CAL™
	X-OHW™	XP-870 LRRB™
FREQUENCY	915MHz	
POWER OUT	250 mW	
ANTENNA	Internal	
RANGE	1,312ft (400m)	
WATER RESISTANT	Not submersible	
OPERATING TEMPERATURE RANGE	0° to 130°F (-17° to 54°C)	
POWER SUPPLY	Four (04) AA alkaline 1.5V 1100mAh capacity replaceable batteries	
UNIT STORAGE/ SHIPPING	WEIGHT³	10oz. / 283.49g.
	LENGTH	5.5in. / 13.97cm.
	WIDTH	3.75in. / 9.52cm.
	HEIGHT	1.625in. / 4.127cm.
FCC Part 15.247 compliant		
¹ Channels are user-selectable; all X-MIT transmitters are shipped from the factory on Channel A. If two X-MITs are used in close proximity, they should be set to different channels to prevent interference with one another.		
² Custom channel configurations available upon request.		
³ Without batteries. Batteries should be removed before shipping or long-term storage.		